

1080P Intelligent Pedestrian & Vehicle Detecting and Warning Camera with Blind Spot Information System

AI



—— Model No.: ADA38 ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- Complied with UN ECE R159 MOIS testing requirements, effectively enhancing commercial vehicle driving safety and protecting vulnerable road users
- Support AHD/CVBS/fast ethernet output and RTSP, ISO17215 and other network protocols. Strong compatibility and wide application range
- It can identify pedestrians and vehicles such as cyclists, electric bikers, and pedestrians on foot. Pedestrian and vehicle detection and warning function.
- IP69K waterproof, dustproof, shock resistant and durable in use, offering high quality images, anti-vibration rating: ISO 16750-3(5.9G).
- Detection range: Side view: 0.5~30m; Horizontal narrow Angle: 0.5~30m; Horizontal wide Angle: 0.5~20m; Downward view: 8m/10m
- High definition 1080P video output, with alarming frame, giving timely warnings to drivers.
- Supporting audio alarm output, sending real-time alarming to drivers.
- Lens parameters: Side view: 6mm/ 70° ; Horizontal narrow Angle: 6mm/70° ; Horizontal wide Angle: 2.3mm/150° ; Downward view: 1.45mm/200° ; 1.99mm/170°
- USB2.0 interface, connected to Wi-Fi modules and USB.
- Easy calibration done by phones through a web link
- Automatic upgrade via USB

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

Effective Pixels	1920 (H) x1080 (V)
Pixel Size	2.8μmx2.8μm
Frame Rate	25/30
Scanning System	Progressive Scanning
Sync. System	Internal
Resolution	1080p
Video output	1.0Vp-p, 75Ohm
Gamma Consumption	0.45
Signal to Noise Ratio	38dB
White Balance	Auto
Exposure	Auto
Power Supply	DC10~32V
Operating temp. & humidity	-20℃~70℃,RH95%MAX.
Storage temp. & humidity	-30℃~80℃,RH95%MAX.
Waterproof Rating	IP69K
Anti-vibration	ISO 16750-3 2012 (5.9G)
Viewing Angle	Front / side view: 70° (Horizontal) Rear view: 150° (Horizontal) Bird view: 200° (Horizontal)
Audio	YES
Minimum Illumination	0.01Lux
Detection Distance	Vertical side view:0.5~30m Horizontal narrow Angle: 0.5~30m Horizontal wide Angle: 0.5~20m Downward view: 8m/10m

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Image mode	Mirror/Normal image switchable
Output mode	AHD/CVBS/Fast ethernet
Network protocol	RTSP/ISO17215

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

