

## 1080P 2.4GHz Digital Wireless Forklift Camera



—— Model No.: HDW814P ——

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Features

### 【1080P High Definition】

1080P CMOS image sensor can help you get a clear view during forklift operation

### 【120M Transmission Distance】

Stable signal , up to 120 meters wireless transmission distance

### 【Laser Positioning】

Built-in laser positioning line helps the driver to accurately operate the fork, so as to avoid damage to the goods

### 【62° Viewing Angle】

Wide enough visual range can help solve blind spots problems

### 【Magnetic housing】

No need for wiring, time-saving and effortless.

### 【Waterproof & Shock-resistant】

IP69K waterproof, dustproof, shock resistant, durable and fit for forklift to work outside

### 【Easy Power Supply】

No additional power wiring installation, can be powered by external battery.

### 【Pinhole Lens】

The glass outside the lens is relatively small, which can protect the lens well and prevent collisions with other objects such as sawdust, extending the it's lifespan.

### 【Mini appearance】

The camera is compact and mini in size, and can be easily installed on a slim forklift arm.

## STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Specification

|                                      |                                    |
|--------------------------------------|------------------------------------|
| Image Device                         | 1/2.9" CMOS                        |
| Effective Pixels                     | 1920 (H) x 1080 (V)                |
| Signal to Noise Ratio                | 38dB                               |
| White Balance                        | Auto                               |
| BLC                                  | Auto                               |
| Dynamic Range                        | 81dB                               |
| Operation Frequency                  | 2408MHz-2478MHz                    |
| Transmission Distance (Barrier Free) | 120m (Max)                         |
| Receiving Sensitivity                | -78dBm                             |
| Video Code                           | H.264                              |
| Transmission Power                   | FCC: ≤26dBm CE: ≤20dBm MIC: ≤10dBm |
| Modulation                           | FHSS                               |
| Delay                                | 130ms                              |
| RF Bit Rate                          | 12Mbps                             |
| Operating Temp. & Humidity           | -20℃ ~ 70℃, RH95%MAX.              |
| Storage Temp. & Humidity             | -30℃ ~ 80℃, RH95%MAX.              |
| Minimum Illumination                 | 0Lux/0.1Lux                        |
| Power Supply                         | DC10-32V                           |
| Power Consumption                    | Day: 1.8W-2.5W Night: 3.6W-4.3W    |
| Night Vision Distance                | 3-5M                               |
| Waterproof Rating                    | IP69K                              |
| Audio                                | No                                 |
| Viewing Angle                        | 62°                                |
| Heater                               | No                                 |

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



|                 |               |
|-----------------|---------------|
| IR-Cut Function | No            |
| Image Mode      | Mirror/Normal |

**STONKAM CO., LTD**

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)

