

Waterproof 7 inch HD digital wireless monitor



—— Model No.: HDW125Q ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- Support 4CH wireless camera and wireless transmitter.
- The wireless vehicle monitoring monitor adopts IP66 waterproof shell, and the antenna is built in, which is beautiful and durable. The wireless monitoring camera on the vehicle is waterproof IP69K, no matter whether it is rainy, snowy or foggy, the camera will not be affected.
- A variety of monitors modes, quad view, double view and single view to meet various monitoring needs and reduce blind spots.
- Manual and automatic pair are supported, and the setting is quick and simple. After pairing, you only need to connect the power supply in the vehicle to work.
- Supporting 1080P/720P camera input.
- The operation is more convenient, simple and quick, more durable and smoother, and the service life is prolonged.
- Support 5 trigger input-wires, includes 4 channel single view trigger display and 1 channel split view trigger display, and the split view image can be set flexibly. In addition, the trigger for time to return the main display and triggering priority of 5 trigger input-wires can be configurable.
- Auto-dim lighting control; screen brightness decreases automatically after the environment gets dark for 3 seconds.
- Auto scan function available, each channel can turn on or off auto scan function and adjust the scan time from 5 to 60 seconds.
- Rear view parking lines can be configured.
- IPS Screen: Pixel 1024x600, high contrast, high brightness, authentic colours, so you can get clearer, sharper and more detailed pictures.

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

LCD Dimension	7"
Resolution	1024x 3 (RGB) x600
Contrast	700:1
Brightness	1000cd/m ²
Viewing Angle	U:85 / D:85, R/L:85
Aspect Ratio	16:9
Channel	4 channels
Operating Frequency	2408MHz ~ 2478MHz(ISM band)
Receiving Sensitivity	-78dBm
Transmission Power	FCC≤26dBm CE≤20dBm MIC≤10dBm
Decompression Form	H.264
Modulation	FHSS
Delay	130ms
Transmission Distance	FCC≤300 M CE≤200 M MIC≤60 M
System Format	PAL / NTSC
Power Supply	DC 10-32V
Power Consumption	Max.10W
Loudspeaker	1.5W/8Ω
Operating Temp. & Humidity	-20~+70°C,RH90%MAX
Storage Temp. & Humidity	-30~+80°C,RH90%MAX

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

