

## 1080P Auto Side View Camera IP69K Waterproof Side Camera



—— Model No.: FHD410 ——

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Features

This side camera features:

- Flexible installation places
- 1080P high definition
- IP69K waterproof
- Wide viewing angle: 150°
- Night vision distance: 3-5m (16.40ft)
- Wide power supply: DC 12V
- Anti-vibration: ISO 16750-3 2012 (5.9G)
- Working temperature: -20° C ~ +70° C

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Specification

|                            |                                              |
|----------------------------|----------------------------------------------|
| Image Device               | 1/2.9" CMOS                                  |
| Frame Rate                 | 25 fps / 30 fps                              |
| Effective Pixels           | 1920(H) x 1080(V)                            |
| Pixel Size                 | 2.8 $\mu\text{m}$ $\times$ 2.8 $\mu\text{m}$ |
| Scanning System            | Progressive Scanning                         |
| Sync. System               | Internal                                     |
| Resolution                 | 1080P                                        |
| Video Output               | 1.0Vp-p, 75Ohm                               |
| Gamma Consumption          | 0.45                                         |
| AGC                        | Auto                                         |
| Signal to Noise Ratio      | Better than 52dB                             |
| White Balance              | Auto                                         |
| Electronic Shutter         | 1/25 (1/30)~1/50,000 Seconds                 |
| BLC                        | Auto                                         |
| Operating Temp. & Humidity | -20℃~70℃, RH 95% MAX.                        |
| Storage Temp. & Humidity   | -30℃~80℃, RH 95% MAX.                        |

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)

