

## HD Intelligent Vehicle IP Camera With Pedestrian Detection



—— Model No.: ADA32N ——

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Features

### 【Support Multiple Network Protocols】

Including ONVIF, RTSP,ISO17215, etc., facilitating interconnection and integration with other devices to empower the monitoring system

### 【5MP High-Definition Safety Warning】

The pixel resolution of the camera can reach up to 5 megapixels,empowering it with higher accuracy in capturing details. Coupled with the display's pedestrian and vehicle tracking overlay and alert boxes, it significantly enhances driving safety and assistance capabilities.

### 【Pedestrians & Vehicle Detection and Warning】

It can identify pedestrians and vehicles such as cyclists, electric bikers, and pedestrians on foot. Pedestrian and vehicle detection and warning function.

### 【Audio Alarm】

Supporting audio alarm output, sending real-time alarming to drivers.

### 【Support Upgrade Through Network Cable Firmware】

So customers can catch up the latest functional features and optimize device performance

### 【Waterproof & Shock-resistant】

IP69K waterproof, dustproof,shock resistant and durable in use, offering high quality images

## STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Specification

|                         |                                         |
|-------------------------|-----------------------------------------|
| Anti-vibration          | ISO 16750-3 2012 (5.9G)                 |
| Detection Distance      | Front / side view: 0.5~30m (Horizontal) |
|                         | Rear view: 0.5~20m (Horizontal)         |
|                         | DC10V~32V                               |
| Consumption (12V IN)    | 150mA(IR light off)                     |
|                         | 700mA(IR light on)                      |
| Frame Rate              | 25/30                                   |
| Output signal           | AHD(1.0Vp-p, 75Ohm)                     |
| Resolution              | 2688 (H) x 1944 (V)                     |
| Viewing Angle           | 120° (Horizontal)                       |
|                         | 85°(Vertical)                           |
| Audio Output            | Warning sound signal output             |
| Communication Interface | USB 2.0 (for software upgrade)          |
| Cable Length            | 3M                                      |
| Operating Temperature   | -20 ~ +70℃                              |
| Storage Temperature     | -30 ~ +80℃                              |
| Waterproof Rating       | IP69K                                   |
| Dimension               | 95 x 60 x70mm                           |
| Weight                  | 500g                                    |
| Housing Color           | Black                                   |
| Output mode             | CVBS/Fast ethernet                      |
| Network protocol        | RTSP/ISO17215                           |

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)

