

9 inch HD vehicle quad-view trucks buses passenger cars reversing image display screen



—— Model No.: HD146D ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- IPS screen: HD IPS screen, high resolution, high brightness
- Multi-display modes: Supporting 4 CH HD camera input, display mode supports single view, dual views, triplex views, quad views, trefoil view, Y view, H view, PIP view and other views
- Mirror image function: the parameter of each CH image effect could be adjusted individually, supporting horizontal mirror image and vertical flip display
- Wide power supply: 10-32V wide power supply input supports 12V or 24V automobile battery, reducing the troubles of mismatching voltage and suitable for many scenarios, such as indoor/outdoor security systems, vehicle and ship surveillance
- Reversing marking line: Able to set reversing marking line, adjusting and calibrating freely
- Backlight adjustment: Backlight brightness supports 60-level manual adjustment and 2-level ambient light automobile adjustment
- Touch button: Supporting capacitive touch screen; Icon menu operation; Supporting some gestures
- Multiple languages: Multi languages available, able to be customized according to users' requirements
- Multiple formats: Multiple video formats available to cameras:
1080P30/1080P25/720P30/720P25/PAL/NTSC
- Automatic scan: Automatic scan available, scanning channel and scanning time can be choosed
- Triggering function: 5 trigger lines input, trigger line definition, trigger delay and priority can be adjusted freely
- Other functions: Easy to install and operate, with innovative functions

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

Resolution	1024x3(RGB)x600
Brightness	650 cd/m ²
Contrast	800:1
Viewing Angle	U: 85°/ D: 85°, R/L: 85°
Aspect Ratio	16:9
Operating Temperature	-20~+70℃
Storage Temperature	-30~+80℃
Power Consumption	Max.15W without cameras
Power for Cameras	Max. 4×600mA, 12V
Power Supply	10V-32V
Video Input	4 CH
Audio Input	4 CH

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

