

## 1080P 2.4GHz Digital Wireless Rear View Camera



—— Model No.: HDW871 ——

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Features

- The open transmission distance is as far as 984ft, and the signal is stable and anti-jamming. Even in high-speed or long-distance operation, the monitor will display the surrounding environment in real time, making your driving or operation more convenient without interference, flicker, blur or delay.
- Support PAL/NTSC System
- The device also has night vision function, which provides you with a clear vision for 24 hours.
- With Microphone
- Waterproof: IP69K
- Wide range power supply: DC10-32V
- strong magnetic base and easy installation
- Can be conveniently powered by an external battery

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



## Specification

|                                      |                                 |
|--------------------------------------|---------------------------------|
| Image Device                         | 1/2.9" CMOS                     |
| Effective Pixels                     | 1920 (H) x 1080 (V)             |
| Signal to Noise Ratio                | 38dB                            |
| White Balance                        | Auto                            |
| BLC                                  | Auto                            |
| Dynamic Range                        | 81dB                            |
| Operation Frequency                  | 2408MHz-2478MHz                 |
| Transmission Distance (Barrier Free) | 300m@20dBm                      |
| Receiving Sensitivity                | -78dBm                          |
| Video Code                           | H.264                           |
| Transmission Power                   | 10dBm/20dBm                     |
| Modulation                           | FHSS                            |
| Delay                                | 170ms                           |
| RF Bit Rate                          | 12Mbps                          |
| Operating Temp. & Humidity           | -20℃ ~ 70℃, RH95%MAX.           |
| Storage Temp. & Humidity             | -30℃ ~ 80℃, RH95%MAX.           |
| Minimum Illumination                 | 0Lux/0.1Lux                     |
| Power Supply                         | DC10-32V                        |
| Power Consumption                    | Day: 1.8W-2.5W Night: 3.6W-4.3W |
| Night Vision Distance                | NO IR LED/8-10m/12-15m/20-25m   |
| Waterproof Rating                    | IP69K                           |
| Audio                                | Optional                        |
| Viewing Angle                        | 35°/50°/70°/100°/130°           |
| Heater                               | Optional                        |

### STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)



|                 |               |
|-----------------|---------------|
| IR-Cut Function | Optional      |
| Image mode      | Mirror/Normal |

**STONKAM CO., LTD**

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: [sales@stonkam.com](mailto:sales@stonkam.com)

Website: [www.stonkam.com](http://www.stonkam.com)

