

1080P HD waterproof vehicle wireless transmitter



—— Model No.: WT479 ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- Voltage Input: DC10-32V
- Output power supply for external wired camera
- Video input: CVBS,AHD720P,AHD1080P
- Support pairing with 720P wireless monitors
- Waterproof and dustproof, waterproof rating: IP69K

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

Power Supply	DC 10-32V
Video Input	CVBS / AHD720P/AHD1080P
Operating Frequency	2400- 2483.5MHz
Transmission Distance	100M/200M/300M
Decompression Form	H.264
Transmission Power	10dBm/17dBm/20dBm
RF Bit Rate	MAX.12Mbps
Modulation	FHSS
Delay	200ms
Operating Temp. & Humidity	-20 ~ +70℃ RH90%MAX
Storing Temp. & Humidity	-30 ~ +80℃ RH90%MAX

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



1080P HD waterproof vehicle wireless receiver



—— Model No.: WR480 ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Features

- Voltage Input: DC10-32V
- Support 4 channels: CAM1-CAM4
- Video output: Max.AHD720P
- Support 720P wireless cameras
- Waterproof and dustproof, waterproof rating: IP69K

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

Power Supply	DC 10-32V
Video Output	AHD720P/D1
Operating Frequency	2400- 2483.5 MHz
Transmission Distance	100M/200M/300M
Decompression Form	H.264
Delay	200ms
RF Bit Rate	MAX.12Mbps
Modulation	FHSS
Receiving Sensitivity	-78dBm
Operating Temp. & Humidity	-20 ~ +70℃ RH90%MAX
Storage Temp. & Humidity	-30 ~ +80℃ RH90%MAX

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

