

Automotive Ethernet BroadR-Reach camera



—— Model No.: ADA32E FHD38XSE ——

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Specification

ADA32E

Sensor	1/2.9" 2Mega CMOS
Effective Resolution	1920(H) x 1080 (V)
Pixel	2.8 μm x 2.8 μm
Scanning system	progressive scanning
Electronic Shutter	1/30 (1/25) ~ 1/50,000 second
AGC	Auto
White Balance	Auto
BLC	Auto
Working Temperature	wide-temperature devices:-40°C~+85°C,RH 95% Max. non-wide-temperature devices:-20°C~+70°C,RH 95% Max.
Storage Temperature	wide-temperature devices:-40°C~+95°C,RH 95% Max. non-wide-temperature devices: -30°C~+80°C,RH 95% Max.

FHD38XSE

Sensor	1/2.56 CMOS
Effective Resolution	1280 x 720
Pixel	4.2 μm x 4.2 μm
Scanning system	progressive scanning
Electronic Shutter	1/30 (1/25) ~ 1/50,000 second
AGC	Auto
White Balance	Auto
BLC	Auto
Working Temperature	-40°C~+85°C,RH 95% Max
Storage Temperature	-40°C~+95°C,RH 95% Max

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com



Focal length / Viewing angle	1.99mm/138°
	2.3mm/126°
	6.0mm/52°

STONKAM CO., LTD

Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.

Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977

E-mail: sales@stonkam.com

Website: www.stonkam.com

