STONKAM®
a better vision for the world

Mirrorcam System-Truck & Bus Camera System
（Class II&IV）



—— Model No.: HD260RSL FHD848L ——

STONKAM CO., LTD
Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.
Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977
E-mail: sales@stonkam.com
Website: www.stonkam.com

STONKAM®
a better vision for the world

Features

- 15-inch HD automotive-grade ISP screen with a resolution of 1920*720
- 2 CH HD LVDS camera input, resolution 1920*1536 (3MP), 123dB WDR, LFM supported
- Support recording, pre-recording and multiple types of alarm recording
- Storage medium: 1 * TF card (Max. 512G)
- Comply with the relevant requirements of UN ECE R46 Class II/VI and R151 regulations
- The system is designed to meet the ISO 26262 ASIL-B functional safety requirements
- The system is designed to meet the ISO 21434 automotive cybersecurity requirements
- Support automatic backlight, automatic camera heating & defogging, camera self-cleaning and camera folding
- The system integrates intelligent driving safety functions complying with GSR (General Safety Regulation)
- Support PANNING (cargo box detection and panning algorithm): when the vehicle turns, the cargo box in the image can be detected and the camera view pans accordingly, reducing the occlusion of the cargo box on the monitoring field of view
- Support GPS and G-sensor
- Support touch key control and wired remote controller control
- Wide voltage input: 12-45V, with short-circuit protection

STONKAM CO., LTD
Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.
Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977
E-mail: sales@stonkam.com
Website: www.stonkam.com

STONKAM®
a better vision for the world

Specification

Dimension	15"
Resolution	1920 x 3(RGB) x 720
Contrast	1300:1
Brightness	1200 cd/m²
Viewing Angle	U: 85 / D: 85, R/L: 85
Video Input	2 ch * 1920*1536 LVDS
Video Encoding Format	H.264
Recording	1920*720 30fps 4Mbps
Storage	1 * TF card (MAX. 512G)
Trigger Input	1 ch
Trigger Output	1 ch
CAN	2 ch
USB 2.0	1 ch
GPS	Support
G-Sensor	Support
Remote Controller	Support
Loudspeaker	2W/4Ω
Power Supply	12-45V
Power Consumption	Max. 35W
Operating Temp. & Humidity	-40~+85ºC, RH 90%
Storage Temp. & Humidity	-40~+90℃, RH 90%
Anti-vibration	ISO 16750-3 (2.13G)

STONKAM CO., LTD
Add.: 101, Building 6, No.1 Ruihua Road, Tianhe District, Guangzhou Guangdong, P. R. China.
Tel.: +86 20 6667-0988 Fax.: +86 20 6667-0977
E-mail: sales@stonkam.com
Website: www.stonkam.com